



Mobil Delvac Super 15W-40

Mobil Commercial Vehicle Lube , Ghana

High Performance Diesel Engine Oils

Product Description

Mobil Delvac Super 15W-40 is a high performance diesel engine oil that provides proven protection to diesel engines operating in severe on and off-highway service applications. Mobil Delvac Super 15W-40 is recommended for use in a wide range of heavy-duty applications and operating environments found in the trucking, construction, and agricultural industries.

Features and Benefits

| Features | Advantages and Potential Benefits |
|----------------------------------|---|
| Thermal and oxidation stability | Controls sludge build-up and deposits |
| Excellent detergency/dispersancy | Cleaner engines and longer engine life |
| Stay-in-grade shear stability | Reduced oil consumption and effective wear protection |

Applications

Recommended by ExxonMobil for use in:

- Diesel-powered equipment from leading diesel engine manufacturers
- On-highway light and heavy-duty trucking
- Off-highway industries including: trucking, construction, quarrying, and agriculture
- Mixed fleets

Specifications and Approvals

| |
|---|
| This product is recommended for use in applications requiring: |
| API CF-4 |
| API SG |

Properties and Specifications

| Property | |
|--|------------|
| Grade | SAE 15W-40 |
| Ash, Sulfated, mass%, ASTM D874 | 0.8 |
| Kinematic Viscosity @ 100 C, mm ² /s, ASTM D445 | 14.3 |
| Kinematic Viscosity @ 40 C, mm ² /s, ASTM D445 | 105 |

| Property | |
|---|-------|
| Pour Point, °C, ASTM D97 | -27 |
| Total Base Number, mgKOH/g, ASTM D2896 | 8.2 |
| Viscosity Index, ASTM D2270 | 139 |
| Density @ 15.6 C, g/cm3, ASTM D4052 | 0.880 |
| Flash Point, Cleveland Open Cup, °C, ASTM D92 | 234 |

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

05-2020

ExxonMobil Egypt (S.A.E.)

1097 Cornish El-Neil, Garden City, Cairo, Egypt

+ 20 2 795 4850/60

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

ExxonMobil

Exxon Mobil Esso XTO
EXXON MOBIL CORPORATION

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved